

SAFETY DATA SHEET

1. SUBSTANCE AND SOURCE IDENTIFICATION

Product Identifier

SRM Number: 640e

SRM Name: Line Position and Line Shape Standard for Powder Diffraction (Silicon Powder)

Other Means of Identification: Not applicable.

Recommended Use of This Material and Restrictions of Use

This Standard Reference Material (SRM) is intended for use as a standard for calibration of diffraction line positions and line shapes, determined through powder diffractometry. A unit of SRM 640e consists of approximately 7.5 g of silicon powder bottled under argon.

Company Information

National Institute of Standards and Technology Standard Reference Materials Program 100 Bureau Drive, Stop 2300 Gaithersburg, Maryland 20899-2300

 Telephone:
 301-975-2200
 Emergency Telephone ChemTrec:

 FAX:
 301-948-3730
 1-800-424-9300 (North America)

 E-mail:
 SRMMSDS@nist.gov
 +1-703-527-3887 (International)

Website: http://www.nist.gov/srm

2. HAZARDS IDENTIFICATION

Classification

Physical Hazard: Flammable Solids Category 2

Health Hazard: Not classified.

Label Elements Symbol



Signal Word WARNING

Hazard Statement(s)

H228 Flammable solid.

Precautionary Statement(s)

P210 Keep away from heat, sparks, open flames and hot surfaces – No smoking.

P280 Wear protective gloves, protective clothing and eye protection.

P370 + P378 In case of fire: Use dry powder for metal fires or other appropriate media for extinction.

Hazards Not Otherwise Classified: Not applicable.

Ingredients(s) with Unknown Acute Toxicity: Not applicable.

SRM 640e Page 1 of 6

3. COMPOSITION AND INFORMATION ON HAZARDOUS INGREDIENTS

Substance: Silicon powder, amorphous

Other Designations:

Elemental silicon; polyeristalline silicon powder.

Components are listed in compliance with OSHA's 29 CFR 1910.1200; for the actual values see the Certificate.

Hazardous Component(s)	CAS Number	EC Number (EINECS)	Nominal Mass Concentration (%)
Silicon powder	7440-21-3	231-130-8	100

4. FIRST AID MEASURES

Description of First Aid Measures:

Inhalation: If adverse effects occur, remove to uncontaminated area. If not breathing, give artificial respiration or oxygen by qualified personnel. Seek immediate medical attention.

Skin Contact: Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if needed. Thoroughly clean and dry contaminated clothing before reuse.

Eye Contact: Immediately flush eyes, including under the eyelids with copious amounts of water for at least 15 minutes. Seek immediate medical attention.

Ingestion: If a large amount is swallowed, seek medical attention.

Most Important Symptoms/Effects, Acute and Delayed: Mechanical irritation.

Indication of any immediate medical attention and special treatment needed, if necessary: If any of the above symptoms are present, seek immediate medical attention.

5. FIRE FIGHTING MEASURES

Fire and Explosion Hazards: Dust/air mixtures may ignite or explode. Silicon powder, amorphous is a flammable solid.

Extinguishing Media:

Suitable: Dolomite, dry powder for metal fires, dry sand, graphite, soda ash, sodium chloride.

Unsuitable: Water.

Specific Hazards Arising from the Chemical: None listed.

Special Protective Equipment and Precautions for Fire-Fighters: Avoid inhalation of material or combustion byproducts. Wear full protective clothing and NIOSH approved self-contained breathing apparatus (SCBA).

NFPA Ratings (0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe)

Health = 1 Fire = 3 Reactivity = 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment; see Section 8, "Exposure Controls and Personal Protection".

Methods and Materials for Containment and Clean up: Do not touch spilled material. Notify safety personnel of spills. Collect spilled material in appropriate container for disposal. Isolate hazard area and deny entry. Clean up residue with a high-efficiency particulate filter vacuum.

SRM 640e Page 2 of 6

7. HANDLING AND STORAGE

Safe Handling Precautions: See Section 8, "Exposure Controls and Personal Protection". Use methods to minimize dust.

Storage: Store and handle in accordance with all current regulations and standards. Keep separated from incompatible substances (see Section 10, "Stability and Reactivity").

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits:

Component: Silicon metal powder

NIOSH (REL): 10 mg/m³ TWA (total dust); 5 mg/m³ TWA (respirable dust).

ACGIH (TLV): No exposure limits established.

OSHA (PEL): 15 mg/m³ TWA (total dust); 5 mg/m³ TWA (respirable fraction).

Engineering Controls: Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

Personal Protection: In accordance with OSHA 29 CFR 1910.132, subpart I, wear appropriate Personal Protective Equipment (PPE) to minimize exposure to this material.

Respiratory Protection: If workplace conditions warrant a respirator, a respiratory protection program that meets OSHA 29CFR 1910.134 must be followed. Refer to NIOSH 42 CFR 84 for applicable certified respirators.

Eye/Face Protection: Wear splash resistant safety goggles with a face shield. An eye wash station should be readily available near areas of use.

Skin and Body Protection: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Chemical-resistant gloves should be worn at all times when handling chemicals.

9. PHYSICAL AND CHEMICAL PROPERTIES

Descriptive Properties: Silicon metal powder

Appearance lustrous gray to black **(physical state, color, etc.):** powder, color is moisture

Molecular Formula: sensitive
Si

Molar Mass (g/mol): 28.09

Odor: odorless
Odor threshold: not applicable
pH: not applicable

Evaporation rate (ether = 1):

Melting point/freezing point (°C):

Relative Density:

not available

1410 (2570 °F)

2.33 g/cc (25 °C)

Vapor Pressure: 1 mmHg (1724 °C)
Vapor Density (air = 1): not applicable
Viscosity (cP): not applicable

Solubility(ies):

soluble in nitric
acid/hydrofluoric acid
mixtures, molten alkali

oxides, molten metals,
germanium
insoluble in organic
solvents; insoluble in water,

HCl, HNO₃ and HF not available

(n-octanol/water):
Particle Size 4.1 µm

SRM 640e Page 3 of 6

 160 g/m^3 **Explosive Limits, LEL: Explosive Limits, UEL (Volume %):** not available Flash Point (°C): not applicable Flammability (solid, gas): flammable solid 10. STABILITY AND REACTIVITY Reactivity: Stable at normal temperatures and pressure. **Stability:** X Stable Unstable Possible Hazardous Reactions: Dust/air mixtures may ignite or explode. Conditions to Avoid: Avoid generating dust. Avoid heat, flames, sparks or other sources of ignition. **Incompatible Materials:** Acids, halogens, metal carbide, metal salts, metals, oxidizing materials. Fire/Explosion Information: See Section 5, "Fire Fighting Measures". **Hazardous Decomposition:** Thermal decomposition will produce oxides of silicon. Will Occur X Will Not Occur **Hazardous Polymerization:** 11. TOXICOLOGICAL INFORMATION X Skin **Route of Exposure:** X Inhalation X Ingestion Symptoms Related to the Physical, Chemical and Toxicological Characteristics: Eye, skin and respiratory irritation. Potential Health Effects (Acute, Chronic and Delayed): Inhalation: Acute exposure to inert dust may result in mucous membrane irritation and cough. Chronic exposure to inert dust may result in chronic bronchitis. **Skin Contact:** Contact may cause mechanical irritation. No data listed for chronic exposure. Eye Contact: Dust may cause irritation through mechanical abrasion. No data listed for chronic exposure. **Ingestion:** Ingestion may cause digestive tract irritation. No data listed for chronic exposure. **Numerical Measures of Toxicity:** Acute Toxicity: Not classified. Rat, Oral LD50: 3160 mg/kg Skin Corrosion/Irritation: No data available. Serious Eye Damage/Irritation: Not classified. Rabbit, Eye: 3 mg (mild) **Respiratory Sensitization:** No data available. Skin Sensitization: No data available. Germ Cell Mutagenicity: No data available. Carcinogenicity: Not classified. Listed as a Carcinogen/Potential Carcinogen X No Silicon metal is not listed by NTP, IARC, or OSHA as a carcinogen. Reproductive Toxicity: Not classified. Specific Target Organ Toxicity, Single Exposure: Not classified. Specific Target Organ Toxicity, Repeated Exposure: Not classified.

780 (1436 °F)

not applicable 2355 (4271 °F)

Thermal Stability Properties:

Autoignition Temperature (°C): Thermal Decomposition (°C):

Initial boiling point and boiling range (°C):

SRM 640e Page 4 of 6

12. ECOLOGICAL INFORMATION

Ecotoxicity Data:

Component: Silicon: No data available.

Persistence and Degradability: No data available.

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

Other Adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose of waste in accordance with all applicable federal, state, and local regulations. Silicon subject to disposal regulations: U.S. EPA 40 CFR 262, Hazardous Waste Number: D001

14. TRANSPORTATION INFORMATION

U.S. DOT and IATA: UN1346, Silicon powder, amorphous, Hazard Class 4.1, Packing Group III.

15. REGULATORY INFORMATION

U.S. Regulations:

CERCLA Sections 102a/103 (40 CFR 302.4): Not regulated.

SARA Title III Section 302 (40 CFR 355.30): Not regulated.

SARA Title III Section 304 (40 CFR 355.40): Not regulated.

SARA Title III Section 313 (40 CFR 372.65): Not regulated.

OSHA Process Safety (29 CFR 1910.119): Not regulated.

SARA Title III Sections 311/312 Hazardous Categories (40 CFR 370.21):

ACUTE HEALTH: No. CHRONIC HEALTH: No. FIRE: Yes. REACTIVE: No. PRESSURE: No.

State Regulations:

California Proposition 65: Not listed.

U.S. TSCA Inventory: Listed.

TSCA 12(b), Export Notification: Not listed.

Canadian Regulations:

WHMIS Information: Not provided for this material.

SRM 640e Page 5 of 6

16. OTHER INFORMATION

Issue Date: 29 October 2015

Sources: ChemAdvisor, Inc., SDS *Silicon*, 19 September 2015.

Hazardous Substances Data Bank, National Library of Medicine, *Silicon, Elemental* CAS 7440-21-3, available at http://toxnet.nlm.nih.gov/cgi-bin/sis/search/f?/temp/~IORHxi:1 (accessed Oct 2015).

International Labor Organization International, International Chemical Safety Card (ICSC) database, *Silicon*, available at: http://www.ilo.org/dyn/icsc/showcard.display?p_lang=en&p_card_id=1508 (accessed Oct 2015).

Key of Acronyms:

ACGIH	American Conference of Governmental Industrial	NIOSH	National Institute for Occupational Safety and
	Hygienists		Health
ALI	Annual Limit on Intake	NIST	National Institute of Standards and Technology
CAS	Chemical Abstracts Service	NRC	Nuclear Regulatory Commission
CEN	European Committee for Standardization	NTP	National Toxicology Program
CERCLA	Comprehensive Environmental Response,	OSHA	Occupational Safety and Health Administration
	Compensation, and Liability Act		
CFR	Code of Federal Regulations	PEL	Permissible Exposure Limit
CPSU	Coal Mine Dust Personal Sample Unit	RCRA	Resource Conservation and Recovery Act
DOT	Department of Transportation	REL	Recommended Exposure Limit
EC50	Effective Concentration, 50 %	RM	Reference Material
EINECS	European Inventory of Existing Commercial	RQ	Reportable Quantity
	Chemical Substances		
EPCRA	Emergency Planning and Community Right-to-Know	RTECS	Registry of Toxic Effects of Chemical Substances
	Act		
IARC	International Agency for Research on Cancer	SARA	Superfund Amendments and Reauthorization Act
IATA	International Air Transportation Association	SCBA	Self-Contained Breathing Apparatus
IDLH	Immediately Dangerous to Life and Health	SRM	Standard Reference Material
ISO	International Organization for Standardization	STEL	Short Term Exposure Limit
LC50	Lethal Concentration, 50 %	TDLo	Toxic Dose Low
LD50	Lethal Dose, 50 %	TLV	Threshold Limit Value
LEL	Lower Explosive Limit	TPQ	Threshold Planning Quantity
MSDS	Material Safety Data Sheet	TSCA	Toxic Substances Control Act
NFPA	National Fire Protection Association	TWA	Time Weighted Average
MSHA	Mine Safety and Health Administration	UEL	Upper Explosive Limit
		WHMIS	Workplace Hazardous Materials Information System
			-

Disclaimer: Physical and chemical data contained in this SDS are provided only for use in assessing the hazardous nature of the material. The SDS was prepared carefully, using current references; however, NIST does not certify the data in the SDS. The certified values for this material are given in the NIST Certificate.

Users of this SRM should ensure that the SDS in their possession is current. This can be accomplished by contacting the SRM Program: telephone (301) 975-2200; fax (301) 948-3730; e-mail srmmsds@nist.gov; or via the Internet at http://www.nist.gov/srm.

SRM 640e Page 6 of 6